

WHAT IS CLAIMED IS:

1. A method for retrieving information from a storage medium, comprising:
exposing a first portion of a surface of the storage medium to stimulating light, the
5 stimulating light diffusing in the storage medium under a second portion of the surface
adjacent the first portion, the second portion of the surface being shielded from exposure to
the stimulating light; and
receiving stimulated light corresponding to the information with at least one detector
positioned to receive the stimulated light via the second portion of the surface of the storage
10 medium, the stimulated light being released from the storage medium in response to the
stimulating light diffused under the second portion of the surface.
2. The method of claim 1 further comprising controlling an intensity of the
stimulating light to result in a predetermined distribution of the stimulating light under the
15 second portion of the surface of the storage medium.
3. The method of claim 1 further comprising converting the stimulated light
received by the at least one detector to electronic data corresponding to the information.
- 20 4. The method of claim 1 wherein the stimulating light is transmitted to the
surface of the storage medium using a laser pencil beam, and wherein exposing the first
portion of the surface comprises moving the laser pencil beam relative to the surface of the
storage medium in two dimensions.

5. The method of claim 4 wherein the at least one detector comprises one photodetector, and wherein receiving the stimulated light comprises moving the photodetector relative to the surface of the storage medium in the two dimensions in a manner corresponding to relative motion between the laser pencil beam and the surface, thereby capturing the stimulated light.

6. The method of claim 4 wherein the laser pencil beam is focused to stimulate one pixel corresponding to the second portion of the surface of the storage medium at a time.

7. The method of claim 1 wherein the stimulating light is transmitted to the surface of the storage medium using an array of light emitting diodes, and wherein exposing the first portion of the surface comprises moving the array of light emitting diodes relative to the surface of the storage medium in one dimension.

8. The method of claim 7 wherein the at least one detector comprises a linear array of photodetectors, and wherein receiving the stimulated light comprises moving the array of photodetectors relative to the surface of the storage medium in the one dimension in a manner corresponding to relative motion between the array of light emitting diodes and the surface, thereby capturing the stimulated light.

9. The method of claim 1 wherein the stimulating light uniformly illuminates the first portion of the surface of the storage medium, and wherein exposing the first portion of the surface comprises exposing successive portions of the surface of the storage medium along at least one dimension.

10. The method of claim 1 further comprising placing the at least one detector in contact with the surface of the storage medium.

11. The method of claim 1 further comprising placing the at least one detector at
5 a first distance from the surface of the storage medium.

12. The method of claim 1 wherein the storage medium comprises a turbid material.

13. The method of claim 12 wherein the turbid material comprises a storage-
10 phosphor.

14. The method of claim 1 further comprising inhibiting the stimulating light from impinging upon the at least one detector.

15

15. The method of claim 14 wherein inhibiting the stimulating light comprises interposing a filter between the at least one detector and the surface of the storage medium to filter out the stimulating light.

20

16. A method for retrieving image information captured in a storage-phosphor plate, comprising:

exposing a first portion of a surface of the storage-phosphor plate to stimulating light using an array of light emitting diodes, the stimulating light diffusing in the storage medium under a second portion of the surface adjacent the first portion, the second portion of the
25 surface being shielded from exposure to the stimulating light; and

receiving stimulated light released from the storage-phosphor plate in response to the stimulating light with a linear array of detectors positioned to receive the stimulated light via the second portion of the surface of the storage-phosphor plate, the stimulated light corresponding to the information.

5

17. The method of claim 16 wherein exposing the first portion of the surface comprises moving the array of light emitting diodes relative to the surface of the storage-phosphor plate in one dimension, and wherein receiving the stimulated light comprises moving the array of detectors relative to the surface of the storage-phosphor plate in the one dimension in a manner corresponding to relative motion between the array of light emitting diodes and the surface.

10

18. The method of claim 16 further comprising controlling an intensity of the stimulating light to result in a predetermined distribution of the stimulating light under the second portion of the surface of the storage-phosphor plate.

15

19. The method of claim 16 further comprising converting the stimulated light to electronic data corresponding to the information.

20

20. The method of claim 16 further comprising placing the array of detectors in contact with the surface of the storage-phosphor plate.

21. The method of claim 16 further comprising placing the array of detectors at a first distance from the surface of the storage-phosphor plate.

25

22. The method of claim 16 further comprising inhibiting the stimulating light from impinging upon the array of detectors.

23. The method of claim 22 wherein inhibiting the stimulating light comprises
5 interposing a filter array between the array of detectors and the surface of the storage-phosphor plate.

24. An apparatus operable to store and retrieve information, comprising:
a storage medium operable to capture incident light corresponding to the information;
10 a stimulating light source operable to expose a first portion of a surface of the storage medium to stimulating light such that the stimulating light diffuses in the storage medium under a second portion of the surface adjacent the first portion, the second portion of the surface being shielded from exposure to the stimulating light; and
at least one detector positioned to receive stimulated light via the second portion of
15 the surface of the storage medium, the stimulated light being released from the storage medium in response to the stimulating light diffused under the second portion of the surface.

25. The apparatus of claim 24 further comprising a cassette enclosure having a form factor corresponding to a standard radiographic film cassette, the cassette enclosure
20 having the storage medium, the stimulating light source, and the at least one detector enclosed therein.

26. The apparatus of claim 24 further comprising circuitry operable to convert the stimulated light received by the at least one detector to electronic data corresponding to the
25 information.

27. The apparatus of claim 24 wherein the stimulating light source is operable to transmit a laser pencil beam, the apparatus further comprising an actuator assembly operable to effect relative motion between the laser pencil beam and the surface of the storage medium in two dimensions.

28. The apparatus of claim 27 wherein the at least one detector comprises one photodetector, and wherein the actuator assembly is further operable to effect relative motion between the photodetector and the surface of the storage medium in the two dimensions in a manner corresponding to the relative motion between the laser pencil beam and the surface.

29. The apparatus of claim 27 wherein the stimulating light source is operable to focus the laser pencil beam to stimulate one pixel corresponding to the second portion of the surface of the storage medium at a time.

30. The apparatus of claim 24 wherein the stimulating light source comprises an array of light emitting diodes, the apparatus further comprising an actuator assembly operable to effect relative motion between the array of light emitting diodes and the surface of the storage medium in one dimension.

31. The apparatus of claim 30 wherein the at least one detector comprises a linear array of photodetectors, and wherein the actuator assembly is further operable to effect relative motion between the array of photodetectors and the surface of the storage medium in the one dimension in a manner corresponding to the relative motion between the array of light emitting diodes and the surface.

32. The apparatus of claim 30 wherein the stimulating light source is operable to stimulate one row of pixels corresponding to the second portion of the surface of the storage medium at a time.

5

33. The apparatus of claim 24 wherein the at least one detector is in contact with the surface of the storage medium.

10

34. The apparatus of claim 24 wherein the at least one detector is disposed at a first distance from the surface of the storage medium.

35. The apparatus of claim 24 wherein the storage medium comprises a turbid material.

15

36. The apparatus of claim 35 wherein the turbid material comprises a storage-phosphor.

20

37. The apparatus of claim 24 further comprising at least one filter interposed between the at least one detector and the surface of the storage medium and operable to inhibit the stimulating light from impinging upon the at least one detector.

38. The apparatus of claim 24 wherein the at least one detector and the stimulating light source are mechanically coupled together.

39. The apparatus of claim 38 wherein the at least one detector comprises a linear array of photodetectors and the stimulating light source comprises an array of light emitting diodes.

5 40. The apparatus of claim 39 wherein the linear array of photodetectors and the array of light emitting diodes are configured in a single package.

41. The apparatus of claim 24 further comprising a fiber-optic faceplate interposed between the at least one detector and the surface of the storage medium for transmitting the stimulated light to the at least one detector.

42. The apparatus of claim 41 further comprising a block of optically transmissive material interposed between the stimulating light source and the surface of the storage medium, and in contact with an edge of the fiber-optic faceplate thereby providing protection for the physical integrity thereof.

43. The apparatus of claim 42 wherein the block of optically transmissive material comprises a second fiber-optic faceplate.

20 44. The apparatus of claim 43 wherein the block of optically transmissive material comprises one of glass and plastic.

45. The apparatus of claim 41 wherein the fiber-optic faceplate comprises a plurality of parallel optical fibers, the optical fibers being disposed at a nonzero angle from a direction normal to the surface of the storage medium.

25

46. The apparatus of claim 45 wherein the nonzero angle is less than ten degrees.

47. The apparatus of claim 41 further comprising at least one multi-layer
5 interference filter deposited on at least one side of the fiber-optic faceplate for inhibiting the
stimulating light from reaching the at least one detector.

48. The apparatus of claim 24 further comprising a fiber-optic faceplate
interposed between the stimulating light source and the surface of the storage medium for
10 transmitting the stimulating light to the surface of the storage medium.

49. The apparatus of claim 24 wherein the at least one detector comprises a
photosensitive region at an edge of the at least one detector immediately adjacent the first
15 portion of the surface of the storage medium.

50. The apparatus of claim 24 wherein the at least one detector comprises a
photosensitive region at a first distance from an edge of the at least one detector immediately
adjacent the first portion of the surface of the storage medium.

20 51. The apparatus of claim 24 wherein the stimulating light source comprises an
array of light emitting diodes.

52. The apparatus of claim 51 wherein the array of light emitting diodes
comprises a single row of light emitting diodes.

53. The apparatus of claim 51 wherein the array of light emitting diodes comprises multiple adjacent rows of light emitting diodes.

54. The apparatus of claim 24 wherein the at least one detector comprises a plurality of discrete photodetectors.

55. The apparatus of claim 24 wherein the at least one detector comprises an amorphous array of photodetectors.

56. The apparatus of claim 24 wherein the at least one detector comprises at least one charge-coupled device.

57. The apparatus of claim 56 wherein the at least one charge-coupled device is characterized by a nonlinear photosite response.

58. The apparatus of claim 24 wherein the at least one detector comprises at least one CMOS sensor.

59. The apparatus of claim 24 wherein the at least one detector comprises at least one photomultiplier.

60. An x-ray image capture device, comprising:
a storage-phosphor plate operable to capture incident x-rays corresponding to an image;

a stimulating light source operable to expose a first portion of a surface of the storage-phosphor plate to stimulating light such that the stimulating light diffuses in the storage-phosphor plate under a second portion of the surface adjacent the first portion, the second portion of the surface being shielded from exposure to the stimulating light;

5 a linear array of detectors positioned to receive stimulated light via the second portion of the surface of the storage-phosphor plate and convert the stimulated light to electronic data corresponding to the image, the stimulated light being released from the storage-phosphor plate in response to the stimulating light diffused under the second portion of the surface;

10 an actuator assembly operable to effect relative motion between the surface of the storage-phosphor plate and each of the stimulating light source and the array of detectors in one dimension; and

a cassette enclosure having a form factor corresponding to a standard radiographic film cassette, the cassette enclosure having the storage-phosphor plate, the stimulating light
15 source, the array of detectors, and the actuator assembly enclosed therein.

61. A storage-phosphor plate operable to capture incident x-rays and release latent image energy in response to stimulating light having a first wavelength on the surface of the storage phosphor plate, the storage-phosphor plate having a thickness and including an
20 energy-absorbing dye for absorbing electromagnetic energy having a wavelength in a range including the first wavelength, the energy-absorbing dye having a concentration in the storage-phosphor plate sufficient to attenuate the stimulating light by at least a factor of five through 75% of the thickness of the plate.

62. The storage-phosphor plate of claim 61 wherein the energy-absorbing dye comprises a red-absorbing dye.

63. The storage-phosphor plate of claim 61 wherein the energy-absorbing dye
5 comprises an infrared-absorbing dye.

64. An apparatus operable to store and retrieve information, comprising:
a storage-phosphor plate operable to capture incident x-rays corresponding to the
information, the storage-phosphor plate including a red-absorbing dye for absorbing
10 electromagnetic energy having a wavelength in a range around 680 nm, the red-absorbing
dye having a concentration in the storage-phosphor plate sufficient to attenuate stimulating
light by at least a factor of five through 75% of the thickness of the plate;

a stimulating light source operable to expose the surface of the storage-phosphor
plate to the stimulating light; and

15 at least one detector positioned to receive stimulated light via the surface of the
storage-phosphor plate, the stimulated light being released in response to the stimulating
light.

65. A storage-phosphor plate operable to capture incident x-rays corresponding to
20 an image, the storage-phosphor plate being for use with a scanning apparatus for reading the
image, the storage-phosphor plate being disposed on a foam layer, the foam layer being for
compressing the storage-phosphor plate against the scanning apparatus as the scanning
apparatus moves across the storage-phosphor plate.

66. The storage-phosphor plate of claim 65 wherein the scanning apparatus comprises a linear scanning apparatus which effects one dimensional scanning of the storage-phosphor plate, the linear scanning apparatus being secured at opposing edges of the storage-phosphor plate during scanning, the foam layer increasing in thickness toward the center of the storage-phosphor plate.

67. An apparatus operable to store and retrieve information, comprising:
a storage-phosphor plate operable to capture incident x-rays corresponding to the information, the storage-phosphor plate being disposed on a foam layer;

a stimulating light source operable to expose the surface of the storage-phosphor plate to stimulating light; and

at least one detector positioned to receive stimulated light via the surface of the storage-phosphor plate, the stimulated light being released in response to the stimulating light;

wherein the stimulating light source and the at least one detector are part of a scanning apparatus for reading the information, the foam layer being for pressing the storage-phosphor plate against the scanning apparatus as the scanning apparatus moves across the storage-phosphor plate.

68. A fiber-optic transmission medium for transmitting first electromagnetic energy of a first frequency received from a surface and for absorbing second electromagnetic energy of a second frequency received from the surface, the fiber-optic transmission medium comprising a plurality of optical fibers bundled into a fiber-optic plate and configured for placement in close proximity to the surface, each of the optical fibers comprising a cladding and a core, the cladding comprising a low index host glass doped with a rare earth substance,

and the core comprising a high index host glass doped with the rare earth substance, wherein the optical fibers have a transmission characteristic which peaks at the first frequency and an absorption characteristic which peaks at the second frequency.

5 69. The fiber-optic transmission medium of claim 68 wherein the rare earth substance comprises thulium.

10 70. The fiber-optic transmission medium of claim 68 wherein the first electromagnetic energy comprises blue light and the second electromagnetic energy comprises red light.

15 71. The fiber-optic transmission medium of claim 68 wherein the first electromagnetic energy comprises green light and the second electromagnetic energy comprises infrared light.

 72. An apparatus operable to store and retrieve information, comprising:
a storage-phosphor plate operable to capture incident x-rays corresponding to the information;

20 a stimulating light source operable to expose the surface of the storage-phosphor plate to stimulating light;

 at least one detector positioned to receive stimulated light via the surface of the storage-phosphor plate, the stimulated light being released in response to the stimulating light; and

25 a fiber-optic transmission medium for transmitting the stimulated light and for absorbing the stimulating light, the fiber-optic transmission medium comprising a plurality

of optical fibers bundled into a fiber-optic plate and configured for placement in close proximity to the surface, each of the optical fibers comprising a cladding and a core, the cladding comprising a low index host glass doped with a rare earth substance, and the core comprising a high index host glass doped with the rare earth substance, wherein the optical
5 fibers have a transmission characteristic corresponding to the stimulated light and an absorption characteristic corresponding to the stimulating light.

73. A fiber-optic transmission medium for transmitting first electromagnetic energy of a first frequency received from a surface and for absorbing second electromagnetic energy of a second frequency received from the surface, the fiber-optic transmission medium
10 comprising a plurality of optical fibers bundled into a fiber-optic plate and configured for placement in close proximity to the surface, each of the optical fibers comprising a cladding and a core, the cladding comprising a low index host plastic which includes a dye for absorbing the second electromagnetic energy, and the core comprising a high index host
15 plastic which includes the dye.

74. The fiber-optic transmission medium of claim 73 wherein the dye comprises a red-absorbing dye.

20 75. An apparatus operable to store and retrieve information, comprising:
a storage-phosphor plate operable to capture incident x-rays corresponding to the information;
a stimulating light source operable to expose the surface of the storage-phosphor plate to stimulating light;

at least one detector positioned to receive stimulated light via the surface of the storage-phosphor plate, the stimulated light being released in response to the stimulating light; and

a fiber-optic transmission medium for transmitting the stimulated light and for
5 absorbing the stimulating light, the fiber-optic transmission medium comprising a plurality of optical fibers bundled into a fiber-optic plate and configured for placement in close proximity to the surface, each of the optical fibers comprising a cladding and a core, the cladding comprising a low index host plastic which includes a dye for absorbing the stimulating light, and the core comprising a high index host plastic which includes the dye.

10
76. A fiber-optic transmission medium for transmitting first electromagnetic energy of a first frequency received from a surface and for attenuating second electromagnetic energy of a second frequency received from the surface, the fiber-optic transmission medium comprising a plurality of optical fibers bundled into a fiber-optic plate
15 and configured for placement in close proximity to the surface, each of the optical fibers comprising a cladding and a core, the cladding comprising a reflective material for reflecting and thereby attenuating the second electromagnetic energy.

20 77. The fiber-optic transmission medium of claim 76 wherein the core of the optical fibers comprises glass.

78. The fiber-optic transmission medium of claim 76 wherein the core of the optical fibers comprises plastic.

25 79. An apparatus operable to store and retrieve information, comprising:

a storage-phosphor plate operable to capture incident x-rays corresponding to the information;

a stimulating light source operable to expose the surface of the storage-phosphor plate to stimulating light;

5 at least one detector positioned to receive stimulated light via the surface of the storage-phosphor plate, the stimulated light being released in response to the stimulating light; and

60 a fiber-optic transmission medium for transmitting the stimulated light and for attenuating the stimulating light, the fiber-optic transmission medium comprising a plurality
65 of optical fibers bundled into a fiber-optic plate and configured for placement in close
70 proximity to the surface, each of the optical fibers comprising a cladding and a core, the
75 cladding comprising a reflective material for reflecting and thereby attenuating the
80 stimulating light.

85 80. A front-illuminated charge-coupled device array for generating charge in response to first electromagnetic energy of a first frequency incident on a surface of the array, the array comprising an interference coating on the surface of the array for increasing
90 the extrinsic quantum efficiency of the array with respect to the first electromagnetic energy by reducing reflection of the first electromagnetic energy from the surface.

95 81. The charge-coupled device of claim 80 wherein the interference coating comprises a multi-layer coating.

100 82. The charge-coupled device of claim 80 wherein the interference coating
105 comprises hafnium oxide.

83. The charge-coupled device array of claim 80 wherein the interference coating also decreases the extrinsic quantum efficiency of the array with respect to second electromagnetic energy of a second frequency by increasing reflection of the second electromagnetic energy from the surface.

84. An apparatus operable to store and retrieve information, comprising:
a storage-phosphor plate operable to capture incident x-rays corresponding to the information;
a stimulating light source operable to expose the surface of the storage-phosphor plate to stimulating light; and
a front-illuminated charge-coupled device array for generating charge in response to incidence of stimulated light on a surface of the array, the stimulated light being released in response to the stimulating light, the array comprising an interference coating on the surface of the array for increasing the extrinsic quantum efficiency of the array with respect to the first electromagnetic energy by reducing reflection of the first electromagnetic energy from the surface.

85. A charge-coupled device array for generating charge in response to electromagnetic energy incident on the array, the array having a multi-pinned phase output register which is operable in a burst mode to reduce a dark current associated with the array.

86. An apparatus operable to store and retrieve information, comprising:
a storage-phosphor plate operable to capture incident x-rays corresponding to the information;

a stimulating light source operable to expose the surface of the storage-phosphor plate to stimulating light; and

a charge-coupled device array for generating charge in response to incidence of stimulated light on a surface of the array, the stimulated light being released in response to the stimulating light, , the array having a multi-pinned phase output register which is operable in a burst mode to reduce a dark current associated with the array.

87. A linear charge-coupled device array for generating charge in response to electromagnetic energy incident on the array, the array being one photosite element wide and having a readout amplifier associated therewith for amplifying the charge, the readout amplifier comprising a single-stage transistor amplifier.

88. An apparatus operable to store and retrieve information, comprising:
a storage-phosphor plate operable to capture incident x-rays corresponding to the information;

a stimulating light source operable to expose the surface of the storage-phosphor plate to stimulating light; and

a linear charge-coupled device array for generating charge in response to incidence of stimulated light on a surface of the array, the stimulated light being released in response to the stimulating light, the array being one photosite element wide and having a readout amplifier associated therewith for amplifying the charge, the readout amplifier comprising a single-stage transistor amplifier.

89. A charge-coupled device array for generating charge in response to electromagnetic energy incident on the array, the array comprising first row of first storage

elements and a second row of second storage elements adjacent the first row, the first storage elements having a first width and the second storage elements having a second width greater than the first width, each of the first storage elements corresponding to one of the second storage elements, the charge-coupled device array further comprising a first shift register for
 5 collecting a first portion of the charge generated in the first row and a second shift register for collecting a second portion of the charge generated in the second row.

90. A method for reading the charge generated in the charge-coupled device array of claim 90 comprising:

10 reading the first portion of the charge from the first row using the first shift register;
 reading the second portion of the charge from the second row using the second shift

register; and

for each of the first storage elements,

15 comparing a corresponding part of the first portion of the charge to a threshold value;

where the corresponding part of the first portion of the charge exceeds the threshold value, discarding a corresponding part of the second portion of the charge from the corresponding second storage element, and

20 where the corresponding part of the first portion of the charge is less than the threshold value, combining the corresponding part of the first portion of the charge with the corresponding part of the second portion of the charge from the corresponding second storage element.

91. An apparatus operable to store and retrieve information, comprising:

a storage-phosphor plate operable to capture incident x-rays corresponding to the information;

a stimulating light source operable to expose the surface of the storage-phosphor plate to stimulating light; and

5 a charge-coupled device array for generating charge in response to incidence of stimulated light on a surface of the array, the stimulated light being released in response to the stimulating light, the array comprising first row of first storage elements and a second row of second storage elements adjacent the first row, the first storage elements having a first width and the second storage elements having a second width greater than the first width, each of the first storage elements corresponding to one of the second storage
10 elements, the charge-coupled device array further comprising a first shift register for collecting a first portion of the charge generated in the first row and a second shift register for collecting a second portion of the charge generated in the second row.

15 92. A charge-coupled device array for generating charge in response to electromagnetic energy incident on the array, the array comprising a single row of storage elements, the storage elements comprising first storage elements having a first width and second storage elements having a second width greater than the first width, the single row of storage elements comprising alternating ones of the first and second storage elements, the
20 charge-coupled device array further comprising a shift register for collecting the charge generated in the row of storage elements.

93. A method for reading the charge generated in the charge-coupled device array of claim 92 comprising:

reading the charge from the single row of storage elements using the shift register;

and

for each of the first storage elements,

comparing a first portion of the charge to a threshold value;

5 where the first portion of the charge exceeds the threshold value,

discarding a second portion of the charge from an adjacent second storage element, and

where the first portion of the charge is less than the threshold value,

combining the first portion of the charge with the second portion of the charge
10 from the adjacent second storage element.

94. An apparatus operable to store and retrieve information, comprising:

a storage-phosphor plate operable to capture incident x-rays corresponding to the
information;

15 a stimulating light source operable to expose the surface of the storage-phosphor plate to stimulating light; and

a charge-coupled device array for generating charge in response to incidence of stimulated light on a surface of the array, the stimulated light being released in response to the stimulating light, the array comprising a single row of storage elements, the storage
20 elements comprising first storage elements having a first width and second storage elements having a second width greater than the first width, the single row of storage elements comprising alternating ones of the first and second storage elements, the charge-coupled device array further comprising a shift register for collecting the charge generated in the row of storage elements.

95. A method for collecting electromagnetic energy released from a storage medium using an array of photodetectors, comprising:

collecting portions of the electromagnetic energy from successive rectilinear portions of the storage medium with the array of photodetectors, a center of each rectilinear portion of the storage medium being separated by a sampling pitch;

for each rectilinear portion of the storage medium,

comparing the collected portion of the electromagnetic energy to at least one threshold value; and

adjusting the sampling pitch for the next rectilinear portion of the storage medium based on the comparing.

96. The method of claim 95 wherein the at least one threshold value includes a low signal level threshold value, and the sampling pitch is increased if the portion of the electromagnetic energy is less than the low signal level threshold value.

97. The method of claim 95 wherein the at least one threshold value includes a high signal level threshold value, and the sampling pitch is decreased if the portion of the electromagnetic energy is greater than the high signal level threshold value.

98. A system for collecting electromagnetic energy, comprising:
an array of photodetectors for generating charge in response to incidence of the electromagnetic energy on the array;
an optical transmission medium in close proximity to the array of photodetectors for transmitting the electromagnetic energy to the array of photodetectors; and

an adhesive material for bonding the optical transmission medium to the array of photodetectors, the adhesive material including a dye for absorbing a portion of the electromagnetic energy corresponding to a first frequency.

5 99. The system of claim 98 wherein the dye comprises a fluorescent material, the adhesive material further comprising additional material for absorbing fluorescent light from the fluorescent material.

100. An integrated x-ray image capture and readout system, comprising:
10 a cassette enclosure having a form factor corresponding to a standard radiographic film cassette;

 a storage-phosphor plate operable to capture incident x-rays corresponding to an image;

 a stimulating light source operable to expose a surface of the storage-phosphor plate
15 to stimulating light;

 an array of detectors positioned to receive stimulated light via the surface of the storage-phosphor plate, the stimulated light being released from the storage-phosphor plate in response to the stimulating light; and

 an actuator assembly operable to effect relative motion between the surface of the
20 storage-phosphor plate and each of the stimulating light source and the array of detectors in one dimension;

 wherein the storage-phosphor plate, the stimulating light source, the array of detectors, and the actuator assembly are enclosed in the cassette enclosure.

101. The system of claim 100 further comprising an actuator driver positioned externally to the cassette enclosure and operationally coupled to the actuator assembly via a mechanical link.

5 102. The system of claim 101 wherein the actuator driver is coupled directly to the cassette enclosure.

103. The system of claim 101 wherein the actuator driver is separate from the cassette enclosure.

10 104. The system of claim 101 wherein the mechanical link connects the actuator driver and the actuator assembly via an aperture at a corner of the cassette enclosure.

15 105. The system of claim 104 wherein the mechanical link forms a 135 degree angle with each of two edges of the cassette enclosure joined at the corner.

106. The system of claim 104 wherein the mechanical link is hinged at the corner of the cassette enclosure to allow at least lateral movement of the mechanical link.

20 107. The system of claim 101 wherein the array of detectors is operable to convert the stimulated light to electronic data corresponding to the image, the system further comprising a transmission medium for transmitting the electronic data out of the cassette enclosure, the transmission medium exiting the cassette enclosure via the aperture.

108. The system of claim 100 wherein the actuator assembly is disposed along an edge of the cassette enclosure to maximize an imaging area of the storage-phosphor plate.

109. The system of claim 100 wherein at least a portion of the actuator assembly
5 comprises a radiolucent material.

110. The system of claim 100 wherein the actuator assembly comprises one of a lead screw, a belt, a magnetic linear motor, and an inchworm motor.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210

115. The system of claim 100 further comprising an image capture detection circuitry for sensing whether capture of the incident x-rays is occurring and generating a signal indicative thereof.

5 116. The system of claim 115 wherein the image capture detection circuitry comprises an x-ray detector for detecting some of the incident x-rays.

10 117. The system of claim 115 wherein the image capture detection circuitry comprises a photodiode for detection prompt emission of the storage-phosphor plate in response to the incident x-rays.

118. The system of claim 115 wherein the signal is employed to control actuation of the actuator assembly.

15 119. The system of claim 100 wherein the actuator assembly comprises a magnetic linear motor and the stimulating light source and the array of detectors are configured on a translation stage.

20 120. The system of claim 119 wherein the magnetic linear motor comprises at least one magnet disposed inside and along an edge of the cassette enclosure, and a linear motor actuator coupled to the translation stage.

25 121. The system of claim 100 wherein the form factor of the cassette enclosure corresponds to a standard radiographic film cassette having a set of dimensions corresponding to one of 14" x 17", 14" x 14", 10" x 12", 8" x 10", 35 cm x 43 cm, 35 cm x

35 cm, 20 cm x 40 cm, 18 cm x 43 cm, 13 cm x 18 cm, 13 cm x 30 cm, 18 cm x 24 cm, and 24 cm x 30 cm.

122. A radiographic cassette comprising a storage medium for capturing incident
5 x-rays corresponding to an image, and a radio frequency detector for detecting radio
frequency energy in close proximity to the cassette enclosure, the radio frequency energy
corresponding to patient information to be associated with the image.

123. The system of claim 122 further comprising a radio frequency transmitter
10 disposed outside of the cassette enclosure for generating the radio frequency energy.

124. The system of claim 123 wherein the radio frequency transmitter is included
in one of a wrist band and a badge.

125. An integrated x-ray image capture and readout system, comprising:
15 a cassette enclosure having a form factor corresponding to a standard radiographic
film cassette;

a storage-phosphor plate operable to capture incident x-rays corresponding to an
image;

20 a readout assembly for reading the image from the storage-phosphor plate and
converting the image to electronic information; and

a transmission circuitry for transmitting the electronic information outside of the
cassette enclosure;

25 wherein the storage-phosphor plate and the readout assembly are enclosed in the
cassette enclosure.

126. A method for capturing and reading an x-ray image using the system of claim 125, comprising:

placing the cassette enclosure in an x-ray apparatus for exposure to the incident x-rays;

exposing the storage-phosphor plate to the incident x-rays; and

while the cassette enclosure remains in the x-ray apparatus, reading the electronic information via the transmission circuitry.

127. A charge-coupled device array for generating charge packets in response to electromagnetic energy incident on the array, a photosensitive area of the charge-coupled device comprising a plurality of first regions for storing the charge packets and a plurality of second regions for isolating the charge packets from each other, the second regions occupying at least 60% of the photosensitive area.

128. A charge-coupled device array for generating charge in response to electromagnetic energy incident on the array, the array comprising an output register configured for multi-pinned phase operation and operable in four-phase mode and two-phase mode.

129. A method for reading charge packets generated in a charge-coupled device array comprising a photosensitive area, an output register and a resettable output amplifier comprising:

reading a first charge packet as a first value;

comparing the first value to a threshold value;

where the first value exceeds the threshold value, resetting the output amplifier and reading a second charge packet; and

- where the first value is less than the threshold value, combining the second charge packet with the first charge packet by reading the second charge packet without resetting the
- 5 output amplifier after the first charge packet has been read.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222